

GASCRAFT DEX III ATF

PRODUCT DESCRIPTION

DEX III ATF meets the latest specification of Dexron III for automatic transmissions and power steering fluid. It is designed for the lubrication of torque converters, transmission gear and hydraulic systems used in passenger cars, light trucks and heavy vehicles. Active premium is a low viscosity red dyed oil which performs to the exceptionally high technical standards needed to meet the wide range of lubrication requirements found in transmission systems.

APPLICATIONS

- Car and light truck automatic transmissions
- Heavy duty truck automatic transmissions
- Off-highway plant equipment using full or semi-automatic gearboxes
- Power steering where ATF Dexron III fluid is recommended
- Rotary air compressors requiring anti-wear type compressor oil
- Mobile equipment hydraulic systems

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

PERFORMANCE STANDARDS

DEX III ATF meets the following international specifications:

GENERAL MOTORS	DEXRON III H FLUID	CATERPILLAR	TO-2
FORD	MECRON FLUID	RENK VOITH	
ALLISON	C-4	ZF	TE-ML-09/TE-ML-II/TE-ML-14
MERCEDES BENZ	236.6		

Technical Data*	
Color	Red
Kinematic Viscosity	
mm ² /s @40 °C	50
mm ² /s @100 °C	9
Viscosity Index	Report
Flash Point COC, °C	200 min
Pour Point, °C	-30 max

*The information contained provides the typical properties data considered as representative. Some variation which will not affect performance is possible.