

# Gascraft

## GASCRAFT 5W-40

### PRODUCT DESCRIPTION

**10W-40 SM** is a High Technology Synthetic Blend gasoline engine oil for the latest model passenger cars requiring high performance and specifications. Developed to provide maximum protection for all passenger cars, including high performance cars with low emission engines and catalytic converts fitted to the vehicle. It is available as a SAE 10W-40 viscosity grade to provide maximum fuel saving and to meet long drain requirements. Compatible for all cars running on lead free gasoline.

### APPLICATIONS

- European engines used in long drain, high mileage applications.
- All new makes of passenger cars
- High performance cars with normally aspirated and turbocharged gasoline engines
- Four stroke motorcycle engines where European motor oils are recommended
- Latest model Japanese and US and European manufactured cars

*Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.*

### PERFORMANCE STANDARDS

**GASCRAFT 10W-40** meets the following international specifications:

API	SP/SL/CF	VW	502/505
ACEA	A3/B3/B4	BMW	LONG LIFE
MB	229.3		

Technical Data*	
SAE Grade	10W-40
Density kg/m <sup>3</sup>	0.86
Kinematic Viscosity	
mm <sup>2</sup> /s @40 °C	110
mm <sup>2</sup> /s @100 °C	14.7
Viscosity Index	138
Flash Point COC, °C	215
Pour Point, °C	-33 MAX

\*The information contained provides the typical properties data considered as representative. Some variation which will not affect performance is possible.