

Gascraft

GASCRAFT 20W-50

PRODUCT DESCRIPTION

20W-50 is a modern high technology-based gasoline engine oil meeting and exceeding the latest API standard available in a shear stable viscosity grade. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high performance vehicles. It is suitable for all types of driving conditions and compatible for all cars running on lead free gasoline.

APPLICATIONS

- All new passenger cars
- High performance cars with normally aspirated and turbocharged gasoline engines
- Four stroke motorcycle engines where motor oils are recommended
- Japanese and US manufactured cars
- Light commercial vehicles

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

PERFORMANCE STANDARDS

GASCRAFT 20W-50 meets the following international specifications:

API	SP/SL	VW	501/505
MB	228.1	MACK	EO-K/2
CCMC	G4/D4/PD2	VOLVO	VDS
MAN	271		

Technical Data*	
SAE GRADE	20W-50
Specific Gravity @ 15C	0.875
Kinematic Viscosity mm ² /s @40 °C	180
mm ² /s @100 °C	19.4
Viscosity Index	123
Flash Point COC, °C	220
Pour Point, °C	-24 MAX
Base No. ASTM D2896	6

*The information contained provides the typical properties data considered as representative. Some variation which will not affect performance is possible.