

GASCRAFT 5W-20

PRODUCT DESCRIPTION

5W-20 is an advanced synthetic blend engine oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. **5W-20** meets or exceeds the requirements of the industry's toughest standards and outperforms conventional oils. Its technology comes as standard equipment in many different vehicles, including select high-performance vehicles.

APPLICATIONS

- European engines used in long drain, high mileage applications.
- All new makes of passenger cars
- High performance cars with normally aspirated and turbocharged gasoline engines
- Four stroke motorcycle engines where European motor oils are recommended
- Latest model Japanese and US and European manufactured cars

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

PERFORMANCE STANDARDS

GASCRAFT 5W-20 meets the following international specifications:

API	SP/SL/CF	VW	502/505
ACEA	A3/B3		
MB	229.3		

Technical Data*		
SAE Grade	5W-20	
Density kg/m ³	0.86	
Kinematic Viscosity		
mm²/s @40 °C	49.8	
mm²/s @100 °C	8.9	
Viscosity Index	160	
Flash Point COC, ^o C	205	
Pour Point, ^o C	-36 MAX	
Base No. ASTM D2896	6	

*The information contained provides the typical properties data considered as representative. Some variation which will not affect performance is possible.